

Appliance Comparison Chart

2012 Appliances

	2200	4200	4600	4800	12200	12400	12600	21400	61000
	Small-Office	Enterprise Grade			Data Center Grade			Ultra-High End	
Performance									
SecurityPower	114	114	374	623	738	1046	1861	2003/2900 ¹	3000 to 14600
Firewall Throughput (Gbps)	3	3	9	11	15	25	30	50/100 ¹	Up to 200
VPN Throughput (Gbps)	0.4	0.4	1.5	2	2.5	3.5	7	7	-
IPS Default Profile (Gbps)	2	2	4	6	8	12	17	21	Up to 85
Connections Per Second (K)	25	25	50	70	90	110	130	130/300 ²	Up to 600
Concurrent Sessions (M)	1.2	1.2	1.2	3.5 ²	3.5 ²	3.5 ²	3.5 ²	10 ²	Up to 70
Network									
10/100/1000Base-T/Max Ports	6/6	4/8	8/12	8/16	8/16	10/26	14/26	13/37	NA
1000Base-F SFP (MAX Ports)	NA	4	4	4	4	12	12	36	NA ³
10GBase-F SFP+ (MAX Ports)	NA	NA	NA	2	4	12	12	12	16/32 ³
40GBase-F MAX Ports	NA	NA	NA	NA	NA	NA	NA	NA	4 ³
Expansion Slot	0	1	1	1	1	3	3	3	14
Additional Features									
Software Edition	R71.x, R75.x	R71.x, R75.x	R71.x, R75.x	R71.x, R75.x	R71.x, R75.x	R71.x, R75.x	R71.x, R75.x	R71.x, R75.x	R75.x 64 bit
Storage	250 GB	250 GB	250 GB	250 GB	1+1 500 GB	1+1 500 GB	2x500 GB RAID 1	2x500 GB RAID 1	-
Memory / Max	2/2 GB	4/4 GB	4/4 GB	4/8 GB	4/12 GB	4/12 GB	6/12 GB	12/24 GB	12/24 GB ⁵
LOM Card (Optional)	NA	NA	NA	Yes	Yes	Yes	Yes	Yes	Included
Physical									
Enclosure	Desktop	1U	1U	1U	1U	2U	2U	2U	15U
Dimensions WxDxH (Standard)	8.27 x 8.25 x 1.65 in.	17.25 x 12.56 x 1.73 in.	17.25 x 12.56 x 1.73 in.	17.25 x 16.14 x 1.73 in.	17.25 x 16.14 x 1.73 in.	17.24 x 22.13 x 3.46 in.	17.24 x 22.13 x 3.46 in.	17 x 28 x 3.5 in.	17.5 x 15.16 x 26.25 in.
Dimensions WxDxH (Metric)	210 x 209.5 x 42 mm	439 x 319 x 44 mm	439 x 320 x 44 mm	438 x 410 x 44 mm	438 x 410 x 44 mm	438 x 562 x 88 mm	438 x 562 x 88 mm	431 x 710 x 88 mm	445 x 385 x 660 mm
Weight	2kg (4.4 lbs)	4kg (8.82 lbs)	7.5kg (16.53 lbs)	7.6kg (16.76 lbs)	7.6kg (16.76 lbs)	23.4kg (51.6 lbs)	23.4kg (51.6 lbs)	26kg (57.4 lbs)	Max: 90kg (198.4 lbs)
Power									
Dual, Hot-Swappable Power Supplies	No	No	No	Optional	Optional	Yes	Yes	Yes	Yes ⁶
Power Input	100-240VAC, 47-63Hz								
Single Power Supply Rating	40W	100W	250W	275W	275W	300W	400W	910W	1200W @ 110V, 1600W @ 220V
Power Consumption (Max)	35W	57W	90W	140W	121W	132W	220W	449W	5000W
DC Option	No	No	No	No	No	No	No	No	Yes

¹ With acceleration card in 2012

² With software upgrade in 2012

³ Not including Security Switch Module Management Ports

⁴ Maximum of 256 VLANs per Interface

⁵ Per Security Gateway Module

⁶ Includes 5 AC PSUs or 2 DC PSUs



Appliance Comparison Chart

UTM-1 Appliances

	UTM-1 Edge	UTM-1 Edge N	Series 80	130	270	570	1070	2070	3070
Performance									
SecurityPower	-	-	-	50	50	101	101	101	298
Firewall Throughput	190 Mbps	1.0 Gbps	1.5 Gbps	1.5 Gbps	1.5 Gbps	2.5 Gbps	3 Gbps	3.5 Gbps	4.5 Gbps
VPN Throughput	35 Mbps	200 Mbps	220 Mbps	120 Mbps	120 Mbps	300 Mbps	350 Mbps	450 Mbps	1100 Mbps
IPS Default Profile	35 Mbps	180 Mbps	720 Mbps	1 Gbps	1 Gbps	1.7 Gbps	2.2 Gbps	2.7 Gbps	4 Gbps
Connections Per Second (K)	-	-	-	10	10	19	25	31	54
Concurrent Sessions	8,000	60,000	150,000	600,000	600,000	650,000	650,000	1,100,000	1,100,000
Network									
10/100Base-T/Max Ports	6	-	-	1	-	-	-	-	-
10/100/1000Base-T/ Max Ports	-	6	10	4	4	6	6	8	10
VLANs	32	64	1024	1024 ¹	1024 ¹	1024 ¹	1024 ¹	1024 ¹	1024 ¹
Additional Features									
Software Edition	Embedded NGX	Embedded NGX	R71	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75
Storage	-	-	-	80 GB	160 GB	160 GB	160 GB	160 GB	160 GB
Licensed Users	8/16	32/U	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited
Multisite Management	No	No	No	Standalone	Yes	Yes	Yes	Yes	Yes
Physical									
Enclosure	Desktop	Desktop	Desktop	Desktop	1U	1U	1U	1U	1U
Dimensions (Standard)	1.2 x 8 x 4.8 in.	1.2 x 8 x 4.8 in.	8.75 x 1.75 x 6 in.	10.6 x 5.7 x 1.6 in.	16.8 x 10 x 1.73 in.	16.8 x 10 x 1.73 in.	16.8 x 10 x 1.73 in.	17.4 x 15 x 1.73 in.	17.4 x 15 x 1.73 in.
Dimensions (Metric)	30 x 203 x 122mm	30 x 203 x 122mm	22 x 4.4 x 15.24 cm	270 x 145 x 40mm	429 x 255 x 44mm	429 x 255 x 44mm	429 x 255 x 44mm	443 x 381 x 44mm	443 x 381 x 44mm
Weight	0.7kg (1.6lbs)	0.7kg (1.6lbs)	1.09kg (2.4 lbs)	1.6kg (3.52lbs)	3.7kg (8.1lbs)	3.7kg (8.1lbs)	3.7kg (8.1lbs)	6.5kg (14.3lbs)	6.5kg (14.3lbs)
Power									
Power Input	100/240V, 50/60Hz								
Single Power Supply Rating	18W	18W	12V/2A DC 24W	60W	65W	65W	65W	250W	250W
Power Consumption (Max)	-	-	16.68W	46.9W	26.2W	41.1W	40.1W	63.1W	77.5W

¹ Maximum of 256 VLANs per interface



Power-1 Appliances

	Power-1 5077	Power-1 9077	11067	Power-1 11000 Series 11077	11087
Performance					
SecurityPower	596	1006	up to 1222	up to 1222	1222
Firewall Throughput ¹ (Gbps)	9	16	15	20	30
VPN Throughput (Gbps)	2.4	3.7	3.7	4	4.5
IPS Default Profile ² (Gbps)	7.5	10	10	12	15
Connections Per Second (K)	77	77	77	95	105
Concurrent Sessions (M)	1.2	1.2	1.2	1.2	1.2
Network					
10/100/1000Base-T/Max Ports	10/14	14/18	14/18	14/18	14/18
1000Base-F SFP Max Ports	4	8	8	8	14/18
10GBase-F SFP Max Ports	2	4	4	4	4
Expansion Slots	1	2	2	2	2
VLANs	1024 ³	1024 ³	1024 ³	1024 ³	1024 ³
Additional Features					
Software Edition	R65, R70, R71, R75	R65, R70, R71, R75	R70, R71, R75	R70, R71, R75	R70, R71, R75
Storage	160 GB	2 x 160 GB	2 x 250 GB	2 x 250 GB	2 x 250 GB
LOM Card Option	Yes	Yes	Yes	Yes	Yes
Physical					
Enclosure	2U	2U	2U	2U	2U
Dimensions WxDxH (Standard)	17 x 20 x 3.46 in.	17 x 20 x 3.46 in.	17 x 22.8 x 3.46 in.	17 x 22.8 x 3.46 in.	17 x 22.8 x 3.46 in.
Dimensions WxDxH (Metric)	431 x 509.5 x 88mm	431 x 509.5 x 88mm	431 x 580 x 88mm	431 x 580 x 88mm	431 x 580 x 88mm
Weight	14.5kg (31.9 lbs)	16.5kg (36.3 lbs)	23.4kg (51.6 lbs)	23.4kg (51.6 lbs)	23.4kg (51.6 lbs)
Power					
Dual, Hot-Swappable Power Supplies	Included	Included	Included	Included	Included
Power Input	100~240V, 50~60Hz				
Single Power Supply Rating	250W	400W	500W	500W	500W
Power Consumption (Max)	164.1W	200.7W	253.2W	253.2W	253.2W

¹ Performance data represents the maximum capabilities of the systems as measured under optimal testing conditions. Deployment and policy considerations may impact performance results.

² Test based on real-world traffic blend using the default profile

³ Maximum of 256 VLANs per interface



Appliance Comparison Chart

IP Appliances

	IP282	IP297	IP397	IP567	IP697	IP1287	IP2457
Performance							
SecurityPower	113	113	116	116	268	670	1112
Firewall Throughput (Gbps)	1.5	1.5	3.0	7	7.2/11.7 ²	10.3/17.5 ²	11/30 ²
VPN Throughput (Gbps)	1.0	1.0	677 Mbps	1.7	1.9/ 3.3 ²	1.9/8.3 ²	1.9/8.3 ²
IPS Default Profile (Gbps)	1.4	1.4	2.9	2.9	4	7	9
Connections Per Second (K)	-	30	35	35	55	73	81
Concurrent Sessions	900,000	900,000	1 million	1 million	1 million	1 million	1 million
Network							
10/100/1000Base-T/Max Ports	6	6/8	4/8	4/12	4/16	4/28	4/32
1000Base-F SFP Max Ports	NA	2	4	4	8	12	12
10GBase-F SFP+ Max Ports	NA	NA	NA	NA	6 ¹	10 ¹	10 ¹
Expansion Slots	NA	1	2	2	3	5	5
VLANs	1024 ³	1024 ³	1024 ³	1024 ³	1024 ³	1024 ³	1024 ³
Additional Features							
Software Edition	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75	R65, R70, R71, R75
Storage	40 GB	40 GB	80 GB	80 GB	80 GB	80 GB	80 GB
Disk-Based or Flash	Disk	Disk or Flash	Disk or Flash	Disk or Flash	Disk or Flash	Disk or Flash	Disk or Flash
Memory / Max	1/2	1/2	1/2	1/2	2/4	4/8	4/8
ADP Module	NA	NA	NA	NA	Optional	Optional	Optional
VPN Acceleration	Optional	Optional	Included	Included	Included	Included	Included
Physical							
Enclosure	1U/Half rack	1U/half rack	1U	1U	1U	2U	2U
Dimensions WxDxH (Standard)	8.52 x 18 x 1.71 in.	8.52 x 18 x 1.71 in.	17 x 16 x 1.71 in.	17.23 x 22 x 1.71 in.	17.23 x 24 x 1.71 in.	17.23 x 24.11 x 3.46 in.	17.23 x 24.11 x 3.46 in.
Dimensions WxDxH (Metric)	216 x 457 x 44 mm	216 x 457 x 44mm	432 x 406 x 44mm	438 x 559x 44mm	438 x 610x 44mm	438 x 613 x 88mm	438 x 613 x 88mm
Weight	5.1kg (11.25 lbs)	5.1kg (11.25 lbs)	7.71kg (17.0 lbs)	11.84kg (26.1 lbs)	12.38kg (27.3 lbs)	19.6kg (43.2 lbs)	20.57kg (45.35 lbs)
Power							
Dual, Hot-Swappable Power Supplies	No	No	No	No	Included	Included	Included
Power Input	100/240V 50/60Hz	100/240V, 50/60Hz					
Single Power Supply Rating	133W	133W	150W	225W	250W	700W	700W
Power Consumption (Max)	-	-	100W	165W	-	-	-
DC Option	NA	NA	NA	NA	NA	Optional	Optional

¹ Optional

² Performance without ADP/with ADP

³ Maximum of 256 VLANs per interface



Appliance Comparison Chart

IAS Series Appliances

	IAS ¹ D1	IAS ¹ D2	IAS ¹ D6	IAS ¹ D8	IAS ¹ M2	IAS ¹ M6	IAS ¹ M8	IAS ¹ R2	IAS ¹ R6	IAS ¹ R8
Performance										
Firewall Throughput ² (Gbps)	2	7	16	20	7	16	20	7	16	20
VPN Throughput ² (Gbps)	1.2	2.4	3	4	2.4	3	4	2.4	3	4
IPS Default Profile ³ (Gbps)	-	4	7.1	8.6	4	7.1	8.6	4	7.1	8.6
Concurrent Sessions (M)	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
Network										
10/100/1000Base-T/Max Ports	6/6	6/10	6/10	8/18	4/10	10/10	14/18	4/10	10/10	14/26
VLANs	1024 ⁴	1024 ⁴	1024 ⁴	1024 ⁴	1024 ⁴	1024 ⁴	1024 ⁴	1024 ⁴	1024 ⁴	1024 ⁴
Additional Features										
Software Edition	R71, R75, VSX R67	R71, R75, VSX R67	R71, R75, VSX R67	R71, R75, VSX R67	R65, R70, R71, R75	R71, R75, VSX R67	R71, R75, VSX R67	R71, R75, VSX R67	R71, R75, VSX R67	R71, R75, VSX R67
Storage	2 x 160 GB	2 x 146 GB	2 x 146 GB	2 x 146 GB	2 x 146 GB	2 x 146 GB	2 x 146 GB	2 x 146 GB	2 x 146 GB	2 x 146 GB
UTM Out of the Box	Optional	Optional	Optional	Optional	Yes	Optional	Optional	Optional	Optional	Optional
Multisite Management	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Physical										
Enclosure	1U	1U	1U	2U	1U	1U	2U	1U	1U	2U
Dimensions WxDxH (Standard)	17.6 x 27.5 x 1.69 in.	16.78 x 27.5 x 1.70 in.	16.78 x 27.5 x 1.70 in.	17.5 x 27.5 x 3.38 in.	17.3 x 27.5 x 1.75 in.	17.3 x 27.5 x 1.75 in.	17.5 x 27.5 x 3.36 in.	17 x 30 x 1.70 in.	17 x 30 x 1.70 in.	17.5 x 30.3 x 3.38 in.
Dimensions WxDxH (Metric)	439 x 698 x 43 mm	426 x 692 x 43 mm	426 x 692 x 43 mm	426 x 743 x 86 mm	440 x 698 x 44 mm	443 x 698 x 44 mm	444 x 698 x 84.8 mm	431 x 762 x 43 mm	431 x 762 x 43 mm	445 x 770 x 86 mm
Weight	14.3kg (31.5 lbs)	17.92kg (39.5 lbs)	17.92kg (39.5 lbs)	20.3kg (44 lbs)	16.1kg (35.5 lbs)	16.1kg (35.5 lbs)	26.1kg (57.5 lbs)	17kg (37.5 lbs)	17.92kg (39.5 lbs)	25kg (55 lbs)
Power										
Dual, Hot-Swappable Power Supplies	Optional	Optional	Optional	Included	Optional	Optional	Included	Optional	Optional	Included
Power Input	100~240V, 47~63Hz	100~240V, 50~60Hz	100~240V, 50~60Hz	100~240V, 50~60Hz	100~240V, 50~60Hz	100~240V, 50~60Hz	100~240V, 50~60Hz	100~240V, 47~63Hz	100~240V, 47~63Hz	100~240V, 47~63Hz
Single Power Supply Rating	400W	750W	750W	1200W	650W	650W	1300W	450W	450W	730W
Power Consumption (Max)	180W	212W	212W	342W	180W	212W	342W	178W (min)	178W (min)	504W

¹ IAS = Integrated Appliance Solutions

² Performance data represents the maximum capabilities of the systems as measured under optimal testing conditions. Deployment and policy considerations may impact performance results.

³ Test based on real-world traffic blend using the default profile

⁴ Maximum of 256 VLANs per interface



Bladed Hardware Integrated Appliance Solution (IAS)

	Crossbeam X60	Crossbeam X80-S
Performance		
Throughput (IMIX)	Up to 16 Gbps per APM; up to 75 Gbps per chassis	Up to 16 Gbps per APM; up to 140 Gbps per chassis
Network		
Interfaces / Connections	Up to 32 x 1Gb SFP / 10Gb SFP+ (16 per NPM)	Up to 64 x 1Gb SFP / 10Gb SFP+ (16 per NPM)
Module Support	Up to 2 NPM-x, up to 5 APM-x, up to 2 CPM-x; Support 7 modules total	Up to 4 NPM-x, up to 10 APM-x, up to 2 CPM-x; Support 14 modules total
Additional Features		
Check Point Software	Security Gateway R70, R70 HCC Release, R70 IPv6 Pack, R71 and R75.20; VPN-1 Power VSX R65, R67 & R68; Firewall-1 GX 4.0, 5.0	
Supported Operating System	XOS 7.2.1, 7.3.0.3, 8.0.1, 8.1.0, 8.5.0, 9.0, 9.5 & 9.6	
High Availability Options	Single or Dual System High Availability	
Processors	4-Core, 8-Core or 12-Core Application Processor Module (APM) options	
System Memory	Up to 24GB per Application Processor Module (APM)	
Disk Size	Up to 2 x 450 GB HDD with RAID 1 per Application Processor Module (APM)	
Management	X-Series Management System (XMS), Greenlight Element Manager (GEM), Command line interface (CLI) with automated workflow system (AWS), SNMP v1, v2, v3 and NetFlow v5, v9, v10 support	
Physical		
Form Factor / Size	13.5" H, 17.5" W, 19" D	29" H, 17.5" W, 17.5" D
Environment	Temperature 0 to 40°C (32-104°F); Humidity: 10% - 90% non-condensing	
Certification	Network Equipment Building System (NEBS) Compliant; Under evaluation for Common Criteria EAL4+	
Chassis Regulatory Compliance	RoHS, UL 60950, IEC 950, FCC 47 CFR Part 15 Class A, EN 55022 : EN 55024, VCCI V-3 : AS/NZS 3548 : 1995 : CNS 13438 Class A	
Green IT Compliancy	High-efficiency power system up to 91 percent, WEEE Directive, ISO 14001, RoHS compliant	
Power		
Power	100-240 VAC 2,700W Rated Maximum	X80-S AC: 100-240 VAC 5,100W Rated Maximum X80-S DC: 48V DC 100A
Status Indicators	Power Supply and Module Active / Failed status LED, Port Link (NPM, CPM), Minor/Major/Critical Alarm LEDs	



Appliance Comparison Chart

VSX Appliances

	VSX 12200 Single Unit	VSX 12200 VSLs	VSX 12400 Single Unit	VSX 12400 VSLs	VSX 12600 Single Unit	VSX 12600 VSLs	VSX 21400 Single Unit	VSX 21400 VSLs
Performance								
Firewall Throughput (Gbps)	15	20	25	45	30	50	50	85
VPN Throughput (Gbps)	2.5	5	3.5	6	6	11	7	12
Concurrent Sessions (M)	1.2	1.6	1.2	1.6	1.2	1.6	1.2	1.6
Network								
10/100/1000Base-T Port / (max)	8/16	16/32	10/26	20/52	14/26	28/52	13/37	26/74
1000Base-F SFP (Max Ports)	4	8	12	24	12	24	12	24
10GBase-F SFP+ (Max Ports)	4	8	12	24	12	24	12	24
Expansion Slot	1	2	3	6	3	6	3	6
VLANs	4096	4096	4096	4096	4096	4096	4096	4096
Additional Features								
Software Edition	VSX R67	VSX R67	VSX R67	VSX R67	VSX R67	VSX R67	VSX R67	VSX R67
Storage	1 + 1 500 GB	2 x 1 + 1 500 GB	1 + 1 500 GB	2 x 1 + 1 500 GB	2 x 500 GB RAID 1	2 x 2 x 500 GB RAID 1	2 x 500 GB RAID 1	2 x 2 x 500 GB RAID 1
Memory Max	4/12 GB	2 x 4/12 GB	4/12 GB	2 x 4/12 GB	6/12 GB	2 x 6/12 GB	12/24 GB	2 x 12/24 GB
LOM Card Option	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Virtual Systems (Included/Capacity)	5/10	5/10	10/50	10/50	10/150	10/150	10/250	10/250
Physical								
Enclosure	1U	2U	2U	4U	2U	4U	2U	4U
Dimensions WxDxH (Standard)	17.25 x 16.14 x 1.73 in.	17.25 x 16.14 x 3.46 in.	17.25 x 22.13 x 3.46 in.	17.25 x 22.13 x 6.92 in.	17.24 x 22.13 x 3.46 in.	17.25 x 22.13 x 6.92 in.	17 x 28 x 3.5 in.	17 x 28 x 7 in.
Dimensions WxDxH (Metric)	438 x 410 x 44mm	438 x 410 x 88mm	438 x 562 x 88mm	438 x 562 x 176mm	438 x 562 x 88mm	438 x 562 x 176mm	431 x 710 x 88mm	431 x 710 x 176mm
Weight	7.6kg (16.76 lbs)	15.2kg (33.52 lbs)	23.4kg (51.6 lbs)	46.8kg (103.2 lbs)	23.4kg (51.6 lbs)	46.8kg (103.2 lbs)	26kg (57.4 lbs)	52kg (114.8 lbs)
Power								
Dual, Hot-Swappable Power Supplies	Optional	Optional	Yes	Yes	Yes	Yes	Yes	Yes
Power Input	100~240V, 47~63Hz							
Single Power Supply Rating	275W	275W	300W	300W	400W	400W	910W	910W
Power Consumption (Max)	121W	2 x 121W	132W	2 x 132W	220W	2 x 220W	449W	2 x 449W



Appliance Comparison Chart

VSX Appliances continued

	VSX-1 3070 Single Unit	VSX-1 9070 Single Unit	VSX-1 9090 VLS	VSX-1 11000 Single Unit	VSX-1 11000 VLS
Performance					
Firewall Throughput (Gbps)	4.5	14	28	15/20/25	30/40/50
VPN Throughput (Gbps)	1.0	3.6	7.2	3.7/4.0/4.5	7.4/8.0/9.0
Concurrent Sessions (M)	1	1.1	1.6	1.2	1.6
Network					
10/100/1000Base-T/Max Ports	10	14	28	14	28
1000Base-F SFP Max Ports	NA	8	16	8	16
10GBase-F SFP+ Max Ports	NA	4	8	4	8
Expansion Slots	NA	2	4	2	4
VLANs	4096	4096	4096	4096	4096
Additional Features					
Software Edition	VSX R67	VSX R67	VSX R67	VSX R67	VSX R67
Storage	160 GB	2 x 160 GB	4 x 160 GB	2 x 250 GB	4 x 250 GB
LOM Card Option	Yes	Yes	Yes	Yes	Yes
Virtual Systems (Included/Capacity)	5/10	10/150	10/150	10/250	10/250
Physical					
Enclosure	1U	2U	4U	2U	4U
Dimensions (Standard)	17.4 x 15 x 1.73 in.	17 x 20 x 3.46 in.	17 x 20 x 7 in.	17 x 20 x 3.46 in.	17 x 20 x 7 in.
Dimensions (Metric)	443 x 381 x 44mm	431 x 509.5 x 88mm	431 x 509.5 x 176mm	431 x 509.5 x 88mm	431 x 509.5 x 176mm
Weight	6.5kg (14.3 lbs)	16.5kg (36.3 lbs)	33kg (72.6 lbs)	23.4kg (51.6 lbs)	46.8kg (103.2 lbs)
Power					
Dual, Hot-Swappable Power Supplies	No	Yes	Yes	Yes	Yes
Power Input	100/240V, 50/60Hz				
Single Power Supply Rating	250W	400W	400W	500W	500W
Power Consumption (Max)	78W	201W	2 x 201W	253W	2 x 253W



DLP-1 Appliances

	DLP-1 2571	DLP-1 9571
Performance		
Number of Users	1000	5000
Messages / Hour	70,000	350,000
Throughput	700 Mbps	2.5 Gbps
Network		
10/100/1000Base-T/Max ports	6/6	10/14
10/100/1000Base-T/Max ports	NA	8
10GBase-F SFP+ Max Ports	NA	4
Expansion Slots	NA	2
VLANs	1024	1024
Additional Features		
Software Edition	R75	R75
Storage	500GB	2 x 2TB (Mirrored – RAID 1)
LOM Card Option	No	Yes
Bypass Card	Optional	Included
Physical		
Enclosure	1U	2U
Dimensions WxDxH (Standard)	17.4 x 15 x 1.73 in.	17 x 20 x 3.46 in.
Dimensions WxDxH (Metric)	443 x 381 x 44mm	431 x 509.5 x 88mm
Weight	6.5kg (14.3 lbs)	16.5kg (36.3 lbs)
Power		
Dual, Hot-Swappable Power Supplies	No	Yes
Power Input	100 ~ 240V; 50 ~ 60Hz	
Single Power Supply Rating	250W	400W
Power Consumption (Max)	77.5W	200.7W



Software Blades Appliance Comparison Chart

	2205	2207	2208	2210	4205	4207	4208	4210	4607	4608	4610	4807	4808	4810
Security Gateway Software Blades														
Firewall	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Identity Awareness	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IPsec VPN	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Advanced Networking & Clustering	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Mobile Access ¹	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IPS	*	✓	✓	✓	*	✓	✓	✓	✓	✓	✓	✓	✓	✓
Application Control	*	✓	✓	✓	*	✓	✓	✓	✓	✓	✓	✓	✓	✓
DLP	*	*	✓	*	*	*	✓	*	*	✓	*	*	✓	*
URL Filtering	*	*	*	✓	*	*	*	✓	*	*	✓	*	*	✓
Antivirus & Anti-Malware	*	*	*	✓	*	*	*	✓	*	*	✓	*	*	✓
Anti-Spam & Email Security	*	*	*	✓	*	*	*	✓	*	*	✓	*	*	✓
Web Security	*	*	*	*	*	*	*	*	*	*	*	*	*	*
Security Management Software Blades														
Network Policy Management	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Logging & Status	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

¹ Mobile Access for 5 users is included in default package – to extend the package use the Mobile Access packages

Optional Security Management Software Blades available:

SmartWorkflow, Monitoring, Management Portal, User Directory, SmartProvisioning, SmartReporter, SmartEvent, Endpoint Policy Management

✓ = Included * = Optional NA = Not Available



Software Blades Appliance Comparison Chart continued

	12207	12208	12210	12407	12408	12410	12607	12608	12610	21412	61005
Security Gateway Software Blades											
Firewall	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Identity Awareness	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IPsec VPN	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Advanced Networking & Clustering	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Mobile Access ¹	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	NA
IPS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	*
Application Control	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	*
DLP	*	✓	*	*	✓	*	*	✓	*	✓	NA
URL Filtering	*	*	✓	*	*	✓	*	*	✓	✓	*
Antivirus & Anti-Malware	*	*	✓	*	*	✓	*	*	✓	✓	*
Anti-Spam & Email Security	*	*	✓	*	*	✓	*	*	✓	✓	NA
Web Security	*	*	*	*	*	*	*	*	*	*	NA
Security Management Software Blades											
Network Policy Management	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	NA
Logging & Status	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	NA

¹ Mobile Access for 5 users is included in default package – to extend the package use the Mobile Access packages

Optional Security Management Software Blades available:

SmartWorkflow, Monitoring, Management Portal, User Directory, SmartProvisioning, SmartReporter, SmartEvent, Endpoint Policy Management

✓ = Included * = Optional NA = Not Available



Software Blades Appliance Comparison Chart continued

	Series 80	UTM-1 132	UTM-1 134	UTM-1 138	UTM-1 272	UTM-1 274	UTM-1 278	UTM-1 574	UTM-1 578	UTM-1 1075	UTM-1 1078	UTM-1 2075	UTM-1 2078	UTM-1 3075	UTM-1 3078
Security Gateway Software Blades															
Firewall	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IPsec VPN	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Application Control	NA	*	✓	✓	*	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Identity Awareness	NA	*	✓	✓	*	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
IPS	*	*	*	✓	*	*	✓	*	✓	✓	✓	✓	✓	✓	✓
DLP	NA	*	*	*	*	*	*	*	*	*	*	*	*	*	*
URL Filtering	*	*	*	✓	*	*	✓	*	✓	*	✓	*	✓	*	✓
Antivirus & Anti-Malware	*	*	*	✓	*	*	✓	*	✓	*	✓	*	✓	*	✓
Anti-Spam & Email Security	*	*	*	✓	*	*	✓	*	✓	*	✓	*	✓	*	✓
Advanced Networking	NA	*	*	*	*	*	*	*	*	*	*	*	*	*	*
Mobile Access	NA	*	*	*	*	*	*	*	*	*	*	*	*	*	*
Acceleration & Clustering	NA	*	*	*	*	*	*	*	*	*	*	*	*	*	*
Security Management Software Blades															
Network Policy Management	NA	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Endpoint Policy Management	NA	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Logging & Status	NA	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

Optional Security Gateway Software Blades available:

Voice over IP (VoIP), Web Security

Optional Security Management Software Blades available:

SmartWorkflow, Monitoring, Management Portal, User Directory, SmartProvisioning, SmartReporter, SmartEvent, Endpoint Policy Management

✓ = Included * = Optional NA = Not Available



Software Blades Appliance Comparison Chart continued

	Power-1 5077	Power-1 9077	Power-11067	Power-11077	Power-11087
Security Gateway Software Blades					
Firewall	✓	✓	✓	✓	✓
IPsec VPN	✓	✓	✓	✓	✓
Advanced Networking	✓	✓	✓	✓	✓
Acceleration & Clustering	✓	✓	✓	✓	✓
Identity Awareness	✓	✓	✓	✓	✓
IPS	✓	✓	✓	✓	✓
Application Control	✓	✓	✓	✓	✓
URL Filtering	*	*	*	*	*
Antivirus & Anti-Malware	*	*	*	*	*
Anti-Spam & Email Security	*	*	*	*	*
DLP	*	*	*	*	*
Mobile Access	*	*	*	*	*

	IP282	IP297	IP397	IP567	IP697	IP1287	IP2457
Security Gateway Software Blades							
Firewall	✓	✓	✓	✓	✓	✓	✓
IPsec VPN	✓	✓	✓	✓	✓	✓	✓
Application Control	*	✓	✓	✓	✓	✓	✓
Identity Awareness	*	✓	✓	✓	✓	✓	✓
IPS	*	✓	✓	✓	✓	✓	✓
Advanced Networking	*	✓	✓	✓	✓	✓	✓
Acceleration & Clustering	*	✓	✓	✓	✓	✓	✓
URL Filtering	*	*	*	*	*	*	*

Optional Security Gateway Software Blades available: Voice over IP (VoIP), Web Security

✓ = Included * = Optional NA = Not Available

