

## Cisco Intrusion Detection System Services Module (IDSM-2)

Cisco® integrated network security solutions enable organizations to minimize risk and maximize business continuity. The Cisco IDSM-2 for the Cisco Catalyst® 6500/7600 Series scales to multigigabit environments.

Figure 1. Cisco IDSM-2



Security threats have increased in complexity—multigigabit environments and efficient network intrusion security solutions are critical to maintaining a high level of protection. Vigilant protection ensures business continuity and minimizes the effect of costly intrusions. Cisco integrated network security solutions enable organizations to protect their connected business assets and increase the efficiency of intrusion prevention systems. The Cisco IDSM-2 is part of the Cisco Systems® family of intrusion detection and prevention (IDS/IPS) solutions. It works in concert with other Cisco IDS/IPS components to efficiently protect your data infrastructure.

The Cisco IDSM-2 is a services module for the widely deployed Cisco Catalyst chassis. With an installed base in the hundreds of thousands, the Cisco Catalyst chassis is a logical platform for additional services such as firewall, VPN, and IDS/IPS services. This second-generation services module provides unique benefits to customers seeking IDS/IPS attack protection.

### FEATURES AND BENEFITS

Table 1 lists the features of the Cisco IDSM-2 for the Cisco Catalyst 6500/7600 Series.

Table 1. Cisco IDSM-2 Features

Features	Features Details
Performance (passive)	<ul style="list-style-type: none"> <li>• 600 Mbps</li> <li>• 6,000 new TCP connections per second</li> <li>• 6,000 HTTP transactions per second</li> <li>• 60,000 concurrent connections</li> </ul>
Performance (inline)	<ul style="list-style-type: none"> <li>• 500 Mbps</li> <li>• 5,000 new TCP connections per second</li> <li>• 5,000 HTTP transactions per second</li> <li>• 50,000 concurrent connections</li> <li>• Supports up to 500,000 concurrent connections</li> </ul>
Multigigabit scalability	<ul style="list-style-type: none"> <li>• With no slot restriction on Cisco Catalyst 6500/7600 Series chassis, the 1-RU IDSM-2 can scale to up to 8 modules per chassis, providing up to 4 Gbps of inline prevention</li> </ul>
Hot swap modules	<ul style="list-style-type: none"> <li>• IDSM-2 insertion/removal never affects the Cisco Catalyst switch</li> </ul>

Cisco Catalyst chassis benefits	<ul style="list-style-type: none"> <li>• Cisco EtherChannel® load balancing</li> <li>• Supervisor engine and power redundancy</li> <li>• Port density</li> <li>• Combining with other services modules to provide a scalable security solution</li> </ul>
WAN interoperability support	<ul style="list-style-type: none"> <li>• Supports the Cisco FlexWAN module</li> </ul>
Accurate prevention technologies	<ul style="list-style-type: none"> <li>• Advanced false positive reduction features provide confidence in data passed to the internal network by the user-adjustable Meta Event Generator and Risk Rating features</li> </ul>
Multiple capture techniques	<ul style="list-style-type: none"> <li>• Multiple techniques include SPAN/RSPAN; VLAN access control list (ACL) capture combined with shunning; TCP resets when in passive mode; and drop actions when used inline allows</li> <li>• Allows customers to monitor various network segments and traffic while providing timely action to mitigate threats</li> </ul>
VLAN ACLcapture	<ul style="list-style-type: none"> <li>• Cisco is the only vendor to provide an in-switch IDS/IPS solution supplying access to the data stream via VLAN ACL capture</li> </ul>
Flexible deployment	<ul style="list-style-type: none"> <li>• Can be deployed in Cisco Catalyst 6500/7600 Series chassis with a wide range of supervisor engines, running either hybrid Cisco Catalyst OS or Cisco IOS® Software, for distribution across wide and varied installed base networks</li> </ul>
Recommended minimum Cisco IOS Software support for Cisco IPS Sensor Software v5.1	<ul style="list-style-type: none"> <li>• For Cisco IOS Software Release 12.2(18)SFX4, the following features are supported on the Supervisor Engine 2, Supervisor Engine 32, and Supervisor Engine 720: inline VLAN pairing and Cisco EtherChannel load balancing</li> </ul>
Recommended minimum Cisco Catalyst OS support for Cisco IPS Sensor Software v5.1	<ul style="list-style-type: none"> <li>• For Cisco Catalyst OS 8.5(1), the following features are supported on the Supervisor Engine 1, Supervisor Engine 2, Supervisor Engine 32, and Supervisor Engine 720: inline VLAN pairing and Cisco EtherChannel load balancing</li> </ul>
Standardized code base	<ul style="list-style-type: none"> <li>• Uses the same IPS code as the award-winning Cisco IPS 4200 Series appliances, allowing users to standardize on a single management technique</li> <li>• Simplifies and speeds up installation, training, operation, and support</li> </ul>
Optional anti-X integrated services	<ul style="list-style-type: none"> <li>• Partnership with Trend Micro augments Cisco's native signature development to provide the quickest and most complete signature updates for timely recognition and prevention of attacks</li> </ul>
Single device management using CLI or Cisco IPS Device Manager (IDM)	<ul style="list-style-type: none"> <li>• Module can be configured using the CLI, which is available locally or remotely via Telnet or Secure Shell (SSH)</li> <li>• Cisco IDM is a Web-based tool for sensor configuration and management. It can be accessed through Internet Explorer, Netscape, or Mozilla, and is enabled by default to use Secure Sockets Layer (SSL).</li> </ul>
Enterprise management and monitoring	<ul style="list-style-type: none"> <li>• Cisco IPS Event Viewer (IEV) provides event monitoring for up to five IPS sensors</li> <li>• Cisco Security Manager and Cisco Security Monitoring, Analysis, and Response System (Cisco Security MARS) provide world-class management and monitoring for sensor deployments of all sizes</li> </ul>
Physical Dimensions	<ul style="list-style-type: none"> <li>• Height: 3.0 cm (1.2 in.)</li> <li>• Width: 35.6 cm (14.4 in.)</li> <li>• Depth: 40.6 cm (16 in.)</li> <li>• Weight: 2.27 kg (5 lbs)</li> </ul>
Power	<ul style="list-style-type: none"> <li>• Amps: 2.5</li> <li>• Watts: 105</li> <li>• Heat Dissipation: 450 BTUs</li> </ul>
Operating Environment	<ul style="list-style-type: none"> <li>• Operating temperature: 0 to 40°C (32 to 104.5°F)</li> <li>• Non-operating temperature: -20 to 65°C (-4 to 149°F)</li> <li>• Operating relative humidity: 10 to 90% (non-condensing)</li> <li>• Non-operating relative humidity: 5 to 95% (non-condensing)</li> <li>• Operating and non-operating altitude: sea level to 3,050m (10,000 ft.)</li> </ul>

## ORDERING INFORMATION

### Cisco IDSM-2 Part Numbers

Part Number	Description
WS-SVC-IDS2-BUN-K9	Cisco IDSM-2 if purchased as part of a Cisco Catalyst system
WS-SVC-IDS2-BUN-K9=	Cisco IDSM-2 (spare)

### Cisco IDSM-2 Service Part Numbers

Part Number	Description
CON-xxxx-WIDSBNK9	(as part of a Cisco Catalyst system)
CON-xxxx-IDSBNK9	(spare)

Service key for “xx” in the part number:

SU1 = 8 x 5 x next business day	SU2 = 8 x 5 x 4-hour service
SU3 = 7 x 24 x 4-hour service	SU4 = 7 x 24 x 2 x next business day
SU01 = 8 x 5 x 4-hour service onsite	SU02 = 8 x 5 x 4-hour service onsite
SU03 = 7 x 24 x 4-hour service onsite	SU04 = 7 x 24 x 2-hour service onsite

### Current Code and Signature Revision

- Software release: <http://www.cisco.com/cgi-bin/tablebuild.pl/ips5>
- Signature release: <http://www.cisco.com/cgi-bin/tablebuild.pl/ips5-sigup>

### Cisco Catalyst Supervisor Engine Hardware, Software Requirements, and Interoperability

- Supported configurations, visit: <https://tools.cisco.com/qtc/config/html/configureHomeGuest.html> (Cisco.com login required)

## REGULATORY COMPLIANCE

Emissions	FCC Part 15 (CFR 47) Class A, ICES-003 Class A, EN55022 Class A, CISPR22 Class A, AS/NZS 3548 Class A, VCCI Class A with UTP cables, EN55022 Class B, CISPR22 Class B, AS/NZS 3548 Class B, VCCI Class B with FTP cables
Safety	CE marking according to UL 1950, CSA 22.2 No. 950, EN 60950, IEC 60950, TS 001, AS/NZS 3260
Certifications	<ul style="list-style-type: none"><li>• NEBS Level 3 pending (with Cisco Catalyst 7600)</li><li>• Common Criteria Level 2 certified</li></ul>

### Export Restrictions

The Cisco IDSM-2 is classified as a “strong encryption” product and is export restricted. For more information, visit:

<http://www.cisco.com/wwl/export/crypto/tool/>



## **ADDITIONAL INFORMATION**

For product documentation, visit: <http://www.cisco.com/univercd/cc/td/doc/product/iaabu/csids/index.htm>

For more information about Cisco Catalyst 6500 Series Switches, visit: <http://www.cisco.com/go/6000>

For more information about Cisco IPS solutions, visit: <http://www.cisco.com/go/ips/>

For intelligence reports about current vulnerabilities and threats, visit: <http://www.cisco.com/go/mysdn>

For the Cisco IPS online forum, visit: [http://forum.cisco.com/eforum/servlet/NetProf?page=Security\\_discussion](http://forum.cisco.com/eforum/servlet/NetProf?page=Security_discussion)

To download the Cisco IPS Event Viewer, visit: <http://www.cisco.com/cgi-bin/tablebuild.pl/ids-ev>

For more information, on Cisco Security Manager, visit: <http://www.cisco.com/go/csmanager>

For more information on Cisco Security MARS, visit: <http://www.cisco.com/go/mars>

## **SERVICE AND SUPPORT**

Cisco offers a wide range of services programs to accelerate customer success. These innovative services programs are delivered through a unique combination of people, processes, tools, and partners, resulting in high levels of customer satisfaction. Cisco services help you to protect your network investment, optimize network operations, and prepare the network for new applications to extend network intelligence and the power of your business. For more information about Cisco Services, see [Cisco Technical Support Services](#) or [Cisco Advanced Services](#).



**Corporate Headquarters**  
Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 526-4100

**European Headquarters**  
Cisco Systems International BV  
Haarlerbergpark  
Haarlerbergweg 13-19  
1101 CH Amsterdam  
The Netherlands  
www-europe.cisco.com  
Tel: 31 0 20 357 1000  
Fax: 31 0 20 357 1100

**Americas Headquarters**  
Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
www.cisco.com  
Tel: 408 526-7660  
Fax: 408 527-0883

**Asia Pacific Headquarters**  
Cisco Systems, Inc.  
168 Robinson Road  
#28-01 Capital Tower  
Singapore 068912  
www.cisco.com  
Tel: +65 6317 7777  
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on the **Cisco.com Website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus • Czech Republic  
Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel • Italy  
Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal  
Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden  
Switzerland • Taiwan • Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2006 Cisco Systems, Inc. All rights reserved. CCSP, CCVP, the Cisco Square Bridge logo, Follow Me Browsing, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, FormShare, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, the Networkers logo, Networking Academy, Network Registrar, Packet, PIX, Post-Routing, Pre-Routing, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0601R)